

PABCO Prestige®

Technical Data Sheet



PABCO Prestige® is a heavyweight architectural laminated fiberglass shingle designed for durability and performance. Manufactured with a glass mat saturated in asphalt and coated with mineral granules, it is available in multiple colors. The shingle design helps reduce debris accumulation and provides a visually appealing, layered look.

Technical Specifications

Weight per square (nominal)	287 lbs
Weather Exposure	5 5/8"
Offset	5 5/8"
Shingles per square	64
Bundles per square	4
Bundles per pallet	60

Warranty*

Original Homeowner	Limited Lifetime
Subsequent Homeowners	40 Years (fully transferable)
Non-Prorated Coverage	20 Years
Wind Resistance (110/130 mph)	15 Years
Algae Defender (algae resistance)	20 Years

*Single Family Residence only.

For Other Structures, registration information, etc., visit <https://pabcoroofing.com/warranty/>.

For available colors and other details, visit <https://pabcoroofing.com/pabco-prestige/>.

Certifications

- ASTM D3462 – Standard for Asphalt Shingle w/ Fiberglass and Mineral Granules
- ASTM D3018 – Standard for Class A Asphalt Shingle (Type I)
- ASTM D3161 – Wind Resistance Fan-Induced Test Method (Class F)
- ASTM D7158 – Wind Uplift Resistance Test Method (Class H)
- UL 790 / ASTM E108 – Fire Resistance Test Method (Class A)
- UL 2218 – Standard for Impact Resistance of Prepared Roof Covering Materials (Class 4)
- CAN/ULC-S107 – Standard for Methods of Fire Tests of Roof Coverings
- CSA A123.5 – Standard for Made From Glass Felt and Surfaces With Mineral Granules

Compliance

- ESR-1717 – Compliance Verification for Asphalt Shingles (ICC-ES Report)

For installation instructions and other details, visit <https://pabcoroofing.com/technical-documents/>.

